


CUSTOM PAK OPTION: PACKAGED KIT, GLAZING, TAPE APPLIED

STEP 1: Select Glazing

Group A: PPF Pyran Platinum F up to 90 minutes & 2,736 sq in exposed glass (UL-Listed)
3/16" to 1/4" KFRF KeraShield up to 60 minutes & 3,627 sq in exposed glass,
 or 90 minutes & 3534 sq in exposed glass
Thickness
 See Glazing WS WireShield up to 45 minutes & 2856 sq in exposed glass, or 60 minutes &
 Data Sheets 960 sq in exposed glass, or 90 minutes & 552 sq in exposed glass
 For More TEMP Tempered
 Details PYRO Pyroglashield 20 minutes up to 3419 sq in exposed glass



Group B: KFRL KeraShield FRL (5/16") up to 60 minutes & 3627 sq in exposed glass or
> 1/4" Thickness 90 minutes & up to 3534 sq in exposed glass
 See Glass CONTRA45 (1") 45 minute up to 3419 sq in exposed glass
 Data Sheets KFRU Kerashield FRU (3/4") up to 90 minutes & 2736 sq in exposed glass
 For More CONTRA60 (1") 60 minutes & 2685 sq in exposed glass
 Details CONTRA90 (1-1/2") 90 minutes & 3174 sq in exposed glass



Other Glazing Description and Thickness: _____ **Glass:** _____"
 (INSU, BRG, LGShield, ARM, LAMI require separate submittal completed to select a specific model from available choices. Customer service will assist you in selecting the right vision frame for your specialty glazing)



STEP 2: Select Vision Lite Model

Vision Lites for Group A Glazing: VSL* VSLR VWL VLFEZ VLF
 VLFR VLFSG



Vision Lites for Group B Glazing: VSIG VLFEZIG VLFIG VLFS10 VLFS10SP
 Provide Door Thickness for all Models in this Group _____" (Frames are made to fit your glazing)
 (See product data for complete specifications for your vision frame including maximum door thickness)

STEP 3: Select Optional Finishes/Materials/Colors/Mullions

Optional Finishes & Materials: S Stainless Steel G Galvannealed E Zinc-Plated
 (See datasheet for product options. Not all models available in all finishes and materials)
Color Code: _____ **B**-Bronze, **W**-White, **BK**-Black, **S**-Sand, **FB**-Flat Black, **AB**-AMS Beige,
 (Steel Only) **SB**-SC Beige, **SI**-Silver, **G**-Gray, **BA**-Brass
Mullion Code: _____ Select Code from Mullion Submittals. Mullions provided for both sides.



STEP 4: Provide Size of Opening

Dimensions: Width: _____ x Height: _____

STEP 5: Glazing Tape/Packaging/Fasteners

Standard black PVC glazing tape for UL10B Doors **GTAPE200B**
 *VSL Frame Only for UL10C 20 Minute Wood Doors-UL Listed Black PVC glazing tape **GTAPE1/8**
 WS Glazing in sizes greater than 1296 square inches - **FGS3000S90** Glazing Tape.
 Add Intumescent glazing tape for all other UL10C Doors UL-Listed **FGS-4590**.
 Optional Intertek Warnock Hersey Label instead of UL (WS or PPF only)
 Note: UL10C 20 minute wood doors requires FGS-4590 tape for Intertek listing.
 Torx Other Fasteners: _____
 Package Individually Bulk Packaging for Pallet Shipment

See detailed installation instructions to determine which tape is appropriate for the frame selected

Interpretation of Fire and Building codes May Vary. Consult with the Local Authority Having Jurisdiction (AHJ) to determine appropriate standards.

	Distributor:	Quantity:
	Architect:	Only 1 Model Per Page Please
	Contractor:	Version: 5/27/2021
	Project:	Date:

800-554-6077 QUOTES@ACTIVARCPG.COM ORDERS@ACTIVARCPG.COM SALES@ACTIVARCPG.COM
 VISIT WWW.ACTIVARCPG.COM FOR THE MOST UPDATED PRODUCT INFORMATION BEFORE ORDERING © 2021 ACTIVAR CONSTRUCTION PRODUCTS GROUP INC
 MFG: COMMERCE CA, BLOOMINGTON MN • WAREHOUSES: SEE WEBSITE FOR LOCATIONS