

SPECIFICATIONS:

Tub Material: 24 gauge galvanized steel

Trim Material & Style: 20 gauge CRS, fully recessed %"

square edge

Door Material & Style: 20 gauge CRS, full view **Flange Material:** 22 gauge galvannealed steel **Glazing:** 0.090" clear acrylic (8-1/2" x 22-3/4")

Finish: Powder coat white door and trim, painted white tub

Hinge: Continuous hinge opens door 180 degrees, 20 gauge

CRS powder coat white

Hardware: Zinc plated pull handle, roller catch, glass clips &

screws

Rough Opening: 12-13/16" x 26-5/16" x 6-15/16"

Fire Rating: UL classified and labeled up to 2 hours in accordance with UL 1479 (ASTM-E814) and CAN/USC-S115.

Insulation: Wool insulation

ADA Compliant: Cabinet meets 4" maximum protrusion,

locate handle maximum 48" above floor

Compatible Extinguisher: Cosmic 2.5lb. - 10lb., Galaxy 2.5lb -

10lb., Mercury 2.5lb. - 5lb., Sentinel 5lb.

MODEL # BREAKDOWN:

C — Product Line: Fire protection, cabinet

10 — Tub Size: 10-½" x 24" x 6"

1 — Trim and Door Material: CRS, powder coat finish

5 — Trim Style: Fully recessed %" square edge

F — Door Style: Full view, pull handle, roller catch

10 — Door Glazing: 0.090" clear acrylic

FX2 — Fire Rated

Color: All white

REPLACEMENT PARTS:

Tub: TUB-10-5FX2

Trim: T-1015 Door: D-101F

Glazing: G10F10

Hardware Pack: HPFPUS

MODEL #: C1015F10FX2



© 2024 Activar Construction Products Group, Inc.

800-554-6077

sales@activarcpg.com

www.activarcpg.com

9702 Newton Ave S. Bloomington, MN 55431 | Many Locations Nationwide

	Distributor:		Project:
	Contractor:		Approved By:
	Date:	Quantity:	Architect:
	Scale: 1:8.25	Pages: 1 OF 1	Drawing #: C1015F10FX2-SUBMITTAL