
Architectural Series, Fire Protection Cabinet, Ambassador - C1016F10FX2 FE FX2 CABINET, AMBASSADOR, 1-1/2" SQ TRIM, FULL VIEW, CLR ACR,CRS TUB, CRS DR/TRM, ALL WHT, 10 TUB



SPECIFICATIONS:

Tub Material: 24 gauge galvanized steel

Trim Material & Style: 20 gauge CRS, semi-recessed 1-1/2" square edge

Door Material & Style: 20 gauge CRS, full view

Flange Material: 22 gauge galvannealed steel

Glazing: 0.090" clear acrylic (8-½" x 22-¾")

Finish: Powder coat white door and trim, painted white tub **Hinge:** Continuous hinge opens door 180 degrees, 20 gauge CRS powder coat white

Hardware: Zinc plated pull handle, roller catch, glass clips & screws

Rough Opening: 12-13/16" x 26-5/16" x 5-11/16"

Fire Rating: UL classified and labeled up to 2 hours in accordance with UL 1479 (ASTM-E814) and CAN/USC-S115. **Insulation:** Wool insulation

ADA Compliant: Cabinet meets 4" maximum protrusion, locate handle maximum 48" above floor

Compatible Extinguisher: Cosmic 2.5lb. - 10lb., Galaxy 2.5lb -10lb., Mercury 2.5lb. - 5lb., Sentinel 5lb.

MODEL # BREAKDOWN:

C — Product Line: Fire protection, cabinet 10 — Tub Size: 10-½" x 24" x 6" 1 — Trim and Door Material: CRS, powder coat finish 6 — Trim Style: Semi-recessed 1-½" square edge F — Door Style: Full view, pull handle, roller catch 10 — Door Glazing: 0.090" clear acrylic FX2 — Fire Rated - Color: All white

REPLACEMENT PARTS:

Tub: TUB-10-6FX2 Trim: T-1016 Door: D-101F Glazing: G10F10 Hardware Pack: HPFPUS

MODEL #: C1016F10FX2

	800-554-6077	Distributor: Contractor:		Project:		
	sales@activarcpg.com			Approved By:		
	www.activarcpg.com	Date:	Quantity:	Architect:		
9702 Newton Ave S. Bloomington, MN 55431 Many Locations Nationwide		Scale: 1:8.25	Pages: 1 OF 1	Drawing #:	C1016F10FX2-SUBMITTAL	
© 2024 Activar Construction Products Group, Inc.					REV: A	9/24/2024