
Architectural Series, Fire Protection Cabinet, Ambassador - C1017V10FX2 FE FX2 CABINET, AMBASSADOR, 3" RT, VERT DUO, CLR ACR, CRS TUB, CRS DR/TRM, ALL WHT, 10 TUB



SPECIFICATIONS:

Tub Material: 24 gauge galvanized steel

Trim Material & Style: 20 gauge CRS, semi-recessed 3" rolled edge

Door Material & Style: 20 gauge CRS, vertical duo

Flange Material: 22 gauge galvannealed steel

Glazing: 0.090" clear acrylic (8-1/2" x 22-3/4")

Finish: Powder coat white door and trim, painted white tub

Hinge: Continuous hinge opens door 180 degrees, 20 gauge CRS powder coat white

Hardware: Zinc plated pull handle, roller catch, glass clips & screws

Rough Opening: 12-13/16" x 26-5/16" x 4"

Fire Rating: UL classified and labeled up to 2 hours in accordance with UL 1479 (ASTM-E814) and CAN/USC-S115. **Insulation:** Wool insulation

ADA Compliant: Cabinet meets 4" maximum protrusion, locate handle maximum 48" above floor

Compatible Extinguisher: Cosmic 2.5lb. - 10lb., Galaxy 2.5lb - 10lb., Mercury 2.5lb. - 5lb., Sentinel 5lb.

MODEL # BREAKDOWN:

C — Product Line: Fire protection, cabinet
10 — Tub Size: 10-½" x 24" x 6"
1 — Trim and Door Material: CRS, powder coat finish
7 — Trim Style: Semi-recessed 3" rolled edge
V — Door Style: Vertical duo, pull handle, roller catch
10 — Door Glazing: 0.090" clear acrylic
FX2 — Fire Rated
— Color: All white

REPLACEMENT PARTS:

Tub: TUB-10-7FX2 Trim: T-1017 Door: D-101V Glazing: G10F10 Hardware Pack: HPFPUS

MODEL #: C1017V10FX2

	800-554-6077	Distributor:		Project:
	🔀 sales@activarcpg.com	Contractor:		Approved By:
	💮 www.activarcpg.com	Date:	Quantity:	Architect:
9702 Newton Ave S. Bloomington, MN 55431 Many Locations Nationwide		Scale: 1:8.25	Pages: 1 OF 1	Drawing #: C1017V10FX2-SUBMITTAL

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. IS PROHIBITI

REV: A 9/13/2024