

## SPECIFICATIONS:

Tub Material: 24 gauge galvanized steel

Trim Material & Style: 18 gauge stainless steel, semi-

recessed 3" rolled edge

Door Material & Style: 20 gauge stainless steel, full view

Flange Material: 22 gauge galvannealed steel Glazing: 0.090" clear acrylic (8-½" x 22-¾")
Finish: Satin door and trim, painted white tub

Hinge: Continuous hinge opens door 180 degrees, 20 gauge

stainless steel

**Hardware:** Zinc plated pull handle, roller catch, glass clips &

screws

**Rough Opening:** 12-13/16" x 26-5/16" x 4"

**Fire Rating:** UL classified and labeled up to 2 hours in accordance with UL 1479 (ASTM-E814) and CAN/USC-S115.

**Insulation:** Wool insulation

ADA Compliant: Cabinet meets 4" maximum protrusion,

locate handle maximum 48" above floor

Compatible Extinguisher: Cosmic 2.5lb. - 10lb., Galaxy 2.5lb -

10lb., Mercury 2.5lb. - 5lb., Sentinel 5lb.

## MODEL # BREAKDOWN:

C — Product Line: Fire protection, cabinet

10 — Tub Size: 10-½" x 24" x 6"

3 — Trim and Door Material: SS, satin finish

7 — Trim Style: Semi-recessed 3" rolled edge

F — Door Style: Full view, pull handle, roller catch

10 — Door Glazing: 0.090" clear acrylic

FX2 — Fire Rated

## **REPLACEMENT PARTS:**

Tub: TUB-10-7FX2

Trim: T-1037 Door: D-103F

Glazing: G10F10

Hardware Pack: HPFPUS

**MODEL #: C1037F10FX2** 



© 2024 Activar Construction Products Group, Inc.

800-554-6077

sales@activarcpg.com

www.activarcpg.com

9702 Newton Ave S. Bloomington, MN 55431 | Many Locations Nationwide

Distributor: Project:

Contractor: Approved By:

Date: Quantity: Architect:

Scale: 1:8.25 Pages: 1 OF 1 Drawing #: C1037F10FX2-SUBMITTAL