
Architectural Series, Fire Protection Cabinet, Ambassador - C1816G10FX2 FE FX2 CABINET, AMBASSADOR, 1-1/2" SQ TRIM, FL VIEW SAFTLOK, CLR ACR, CRS TUB, CRS DR/TRM, ALL WHT, 18 TUB



SPECIFICATIONS:

Tub Material: 24 gauge galvanized steel

Trim Material & Style: 20 gauge CRS, semi-recessed 1-½" square edge

Door Material & Style: 20 gauge CRS, full view

Flange Material: 22 gauge galvannealed steel

Glazing: 0.090" clear acrylic (8-1/2" x 22-3/4")

Finish: Powder coat white door and trim, painted white tub **Hinge:** Continuous hinge opens door 180 degrees, 20 gauge CRS powder coat white

Hardware: Zinc plated pull handle, Saf-T-Lok™, glass clips & screws

Rough Opening: 12-13/16" x 26-5/16" x 5-3/16"

Fire Rating: UL classified and labeled up to 2 hours in accordance with UL 1479 (ASTM-E814) and CAN/USC-S115. **Insulation:** Wool insulation

ADA Compliant: Cabinet meets 4" maximum protrusion, locate handle maximum 48" above floor

Compatible Extinguisher: Cosmic 2.5lb. - 6lb., Galaxy 2.5lb - 5.5lb., Mercury 2.5lb. - 5lb.

MODEL # BREAKDOWN:

C — Product Line: Fire protection, cabinet
18 — Tub Size: 10-½" x 24" x 5-½"
1 — Trim and Door Material: CRS, powder coat finish
6 — Trim Style: Semi-recessed 1-½" square edge
G — Door Style: Full view, pull handle, Saf-T-Lok™
10 — Door Glazing: 0.090" clear acrylic
FX2 — Fire Rated
— Color: All white

REPLACEMENT PARTS:

Tub: TUB-18-PP Trim: T-1016 Door: D-101G Glazing: G10F10 Hardware Pack: HPFPUS, SL, LC

MODEL #: C1816G10FX2

	800-554-6077	Distributor: Contractor:		Project:
	sales@activarcpg.com			Approved By:
	www.activarcpg.com	Date:	Quantity:	Architect:
9702 Newton Ave S. Bloomington, MN 55431 Many Locations Nationwide		Scale: 1:8.125	Pages: 1 OF 1	Drawing #: C1816G10FX2-SUBMITTAL

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. IS P

REV: A 9/24/2024