



FIRE-RATED, IMPACT SAFETY-RATED GLAZING

FireLite^{NT} & FireLite^{PLUS}

**WE ARE NOW A TECHNICAL GLASS PRODUCTS
(TGP) OEM PARTNER**



Fire-Rated Glazing for use in Door Vision Lites, Side Lites, and Transoms

FEATURES:

- **UL Classified and labeled**
- **Impact safety rated**
- **Protects from fire and impact on both sides of the glass**
- **Fire protective - protects against flames and smoke**
- **Hose stream tested**
- **Large sizes available**
- **3 Year limited warranty for FireLite NT**
- **5 Year limited warranty for FireLite Plus**



ACTIVAR CONSTRUCTION PRODUCTS GROUP INC.

1-800-554-6077 | SALES@ACTIVARCPG.COM

©2024 Activar Construction Products Group, Inc.

FIRELITE NT FIRE RATED 20-180 minutes

FIRE-RATED, IMPACT SAFETY-RATED GLASS CERAMIC WITH SURFACE-APPLIED FILM

FireLite NT is a 3/16" (5 mm) thick fire-rated and impact safety-rated glazing material. It is listed for use in doors, sidelites, transoms and borrowed lites based on rating duration and corresponding maximum exposed area, width and height.



SPECIFICATIONS:

Material: Glass ceramic with ultraHD® technology for improved surface quality and color and a high performance surface-applied fire-rated film

Thickness: 3/16" (5 mm)

Weight: 2.56 psf

Approx. Light Transmission: 88%

Approx. Visible Reflection: 9%

STC: 35

Size:

Minimum: 4" x 4"

Stock Sheet Size: 48" x 96"

RATINGS:

Fire Rating: 20, 45, 60, 90, 180 minutes based on size and application

UL classified and labeled: UL9, UL10B, UL10C, CAN/ULC-S104, CAN/ULC-S106

Impact Safety Rating: CPSC 16CFR 1201 (Cat I & II), ANSI Z97.1

OPTIONS:

Frosted



FIRELITE PLUS FIRE RATED 20-180 minutes

FIRE-RATED, IMPACT SAFETY-RATED LAMINATED GLASS WITH INTERLAYER OF SAFETY FILM

FireLite Plus is a 5/16" (8 mm) thick fire-rated and impact safety-rated glazing material. It is listed for use in doors, sidelites, transoms and borrowed lites. Ideal for applications where protection from damage is a priority.



SPECIFICATIONS:

Material: Laminated glass ceramic with ultraHD® Technology for improved surface quality and color

Thickness: 5/16" (8 mm)

Weight: 4 psf

Approx. Light Transmission: 85%

Approx. Visible Reflection: 9%

STC: 38

Size:

Minimum: 4" x 4"

Stock Sheet Size: 48" x 96"

RATINGS:

Fire Rating: 20, 45, 60, 90, 180 minutes based on size and application

UL classified and labeled: UL9, UL10B, UL10C, CAN/ULC-S104, CAN/ULC-S106

Impact Safety Rating: CPSC 16CFR 1201 (Cat I & II), ANSI Z97.1

Please consult with your AHJ to make sure your glazing complies with local ordinances before ordering.

5-8-2024